


MOSCA®

EXCELLENCE IN STRAPPING SOLUTIONS

EVOLUTION



Picture with
options

SONIXs TRC-6
Fully Automatic Strapping Machine
for Corrugated Cardboards

SoniXs TRC-6

STANDARD FEATURES

- Symmetrical design of the conveying system to the strapping level
- Easy accessibility and tool-free disassembly of strap way components
- Tool-free disassembly of roller system
- Easy operation over digital display in the control panel
- High-end Standard 6 sealing unit
- Ultrasonic sealing system with electronic self calibration
- Bundle positioning via increments by metrical input of the strapping positions
- Pneumatic hold down device with manuel prepositioning
- Transport by aluminium rollers
- Safety circuit for up-stream and down-stream systems
- Open design without protective coverings – CE marking inclusive conformity declaration
- Selector switch for single, double or multiple strapping
- Quick strap coil change
- Fully automatic strap threading
- Defined strap end detection with ejection of remaining strap
- Automatic strap loop ejection when machine cycles without bundle
- Structural coating RAL 5010 gentian blue

OPTIONS

- Traffic light warning system including low strap indication
- Special working height + 200mm
- Special coating according to RAL scale
- Pneumatic backstop with manuel prepositioning
- Table extension
- Floor rails for easy movement

TECHNICAL DATA

PERFORMANCE:

Machine Type	TRC 125	TRC 165	TRC 220	TRC 260
Frame Size	1250x600	1650x600	2200x600	2600x600
Single strapping (up to)	38	35	31	29

STRAPS:

Standard machine grade: 5, 6, 8, 9, 10 or 12 mm wide PP straps

STRAP COIL DISPENSER:

Core Diameter: 200 mm
Core Width: 190 mm
Max. Outside Diameter: 430 mm

ELECTRICITY:

Network data: 100 – 240 V,
50/60 Hz, 1 PH*

Power Consumption: approx. 0.4 kW


* Country specific adaption possible

PNEUMATICS:

Operating Pressure: 6 bar (1/4 inch rapid clutch)
Air Consumption: 3.5 NI/cycle; with pneumatic hold-down device
9.3 NI/cycle; with pneumatic hold-down device and backstop

WEIGHT:

~ 538 kg (1650 x 600 mm, with hold-down device)
~ 640 kg (1650 x 600 mm, with hold-down device and backstop)



03 / 14 Subject to Alterations



MOSCA®
EXCELLENCE IN STRAPPING SOLUTIONS

MOSCA GMBH

Gerd-Mosca-Straße 1
D-69429 Waldbrunn/Germany
Tel.: +49 6274/932-0
Fax: +49 6274/932-400 118
Tel. Tech. Service: +49 6274 / 9 32-146
E-Mail: info@mosca.com
Internet: www.mosca.com

The models of SoniXs TRC-6 are adjustable to one strap width of all quality PP straps between 5 and 12 mm. Obtainable directly from Mosca, produced in one of Europe's most modern manufacturing plants. Combinable with maintenance contracts by Mosca – a one-stop solution.

